



RAIL GRINDING MACHINE RGM 2-24



L & S Luddeneit und Scherf GmbH
Wimmlerstraße 25
D-07806 Neustadt an der Orla
GERMANY

www.l-und-s.de

Tel.: +49-36481-5645-0
Fax: +49-36481-5645-19



The rail grinder RGM 2-24 is a rail-borne machine which is consisted of two wagons and has 24 grinding spindles with independant angular adjustment. Each of the spindles is driven by a frequency-controlled electrical motor. The computer monitored grinding process is controlled with touch pad by the operator inside of the cabin.

The rail grinder ist equipped with an online-measuring system. The digital measuring data for transverse and longitudinal profile are automatically and continuously collected, evaluated an saved.

The rail grinder RGM 2-24 can be used for removing of rolling skin, the elimination of rail corrugations (grooves) and short waves on the rail head as well as for the reprofiling of the rail head on plain track and in turnouts. The grinder is efficient for working in the open and closed scopes of long rail sections for winning the transverse and longitudinal target profile as well as for machining of turnouts.

LUDDENEIT UND SCHERF GMBH

Technical data of the rail grinder RGM 2-24

Length	26.140 mm
Breadth	2.620 mm
Height	3.750 mm
Weight	84,0 t
Gauge	1.435 mm
Axle load (rail)	max. 13 t
Minimum curve radius	travelling: R25 m grinding: R50 m
Numbers of grinding motors	24
Speed of cup stones	max. 5800 rpm, infinitely variable by integrated frequency converter
Max. grinding angle	-25° outside of the rail (field side) +70° inside of the rail (gauge side)
Operation	- computer monitored grinding process - grinding in both directions - availability of 100 grinding programs
Propulsion	electric / optional: hydraulic
Modification of grinding angles	electromechanical control
Feeding mechanism for grinding stone	electromechanical control
Horizontal grinding stone adjusting	electromechanical control
Rail travel speed	65 km/h
Grinding speed	0,5 to 12,0 km/h
Maximum slope	70 %
Vaccum power for grinding dust collection ..	4 x 12.500 m ³ /h
Water tank	2x 5000 liter
Protections	- spark shields continuously adjustable - particle-emission filter for exhaust gases - fire extinguishing system
Options	- online measuring system for transverse profile - online measuring system for longitudinal profile - automatic turnout grinding function - Command Operation Assistant

DEVELOPMENT – DESIGN – MANUFACTURING – SALE – SERVICE

L&S Luddeneit und Scherf GmbH
Wimmerstraße 25
D- 07806 Neustadt an der Orla - Germany

Tel.: +49 (0) 36481-5645-0
Fax: +49 (0) 36481-5645-19

LUDDENEIT UND SCHERF GMBH

